

Professional Line	TH [pro] Modbus
ID No.:	00.08095.100031
Measuring range air temperature:	-40 ... + 70 ° C
Measuring range rel. Humidity:	0 ... 100% r. F.
Accuracy air temperature:	± 0.1 K (0... 60 ° C) • ± 0.2 K (-40... 0 ° C)
Accuracy rel. Humidity:	typ. ± 1.5% (0 ... 80%) r. F.; ± 2% (> 80%) r. F.
Resolution air temperature:	0.1 ° C
Resolution rel. Humidity:	0.1% r. F.
Reaction time:	rel. Humidity (at v = 1.5 m / s): 30 s
Protocols:	Modbus RTU
Interface:	Serial RS 485
Supply voltage:	4.8 ... 33 VDC
Power consumption:	4 mA at 24 VDC • 6 mA at 12 VDC • 11 mA at 4.8 VDC
Dimensions:	H 140 mm x Ø 20 mm
Casing:	Specially coated aluminum • M12 connector plug (4-pin)
Protection class:	IP 65 (housing)
Weight:	approx. 80 g
Accessories (order separately):	00.08141.600000 Sensor shelter with natural ventilation 00.08141.600004 Sensor shelter with artificial ventilation 32.14567.060010 Sensor cable, 15 m, 4-pin, M12 connector 32.14567.060000 Sensor cable, 12 m, 4-pin, M12 connector