



More information on the website
radwag.com/en/info,w1,JVD

HX5.EX-1.4P.600.C 4 Pallet Scale



Functions



Labelling



Plus/Minus Control



Percent Weighing



Parts counting



Newton unit measurement



Statistics



GLP Procedures



Replaceable unit



ALIBI Memory

Datasheet

Metrological parameters	
Maximum capacity [Max]	600 kg
Minimum load	4 kg
Readability [d]	200 g
Tare range	-600 kg
OIML Class	III
Physical parameters	
Display	5" graphic colour

Physical parameters	
Weighing pan dimensions	840×1200 mm
Packaging dimensions	1400×900×430 mm
Net weight	49,8 kg
Gross weight	50 kg
Protection class	IP 65 construction, IP 66/68 indicator
ATEX Certification	II 2G Ex ib IIB T4 Gb
IECEX Certification	Ex ib IIB T4 Gb
Indicator	PUE HX5.EX-1
Communication interface	
Communication interface	2×RS232, RS485
Electrical parameters	
Power supply	100 ÷ 240 V AC 50 / 60 Hz
Power consumption max.	15 W
Environmental conditions	
Operating temperature	-10 ÷ +40 °C
Relative humidity	10% ÷ 85% RH no condensation
Construction	
Construction	mild steel St3S



Accessories

Communication modules

Power Adapters

Software

RAD-KEY
 RADWAG Connect
 RADWAG Development Studio
 R.Barcode

LabVIEW Driver
 R-LAB
 E2R System