


















More information on the website
radwag.com/en/info,w1,ND7

WPY 30/60/PGC/C2/K Scale



Functions

-  Dosing
-  Labelling
-  Plus/Minus Control
-  Percent Weighing
-  Totalizing
-  Parts counting
-  Peak hold
-  Formulation
-  Newton unit measurement
-  Statistics
-  Checkweighing
-  IR sensors
-  Animal weighing
-  Differential weighing
-  Packaged Goods Control
-  ALIBI Memory

Datasheet

Metrological parameters	
Maximum capacity [Max]	30 / 60 kg
Minimum load	200 / 400 g
Readability [d]	10 / 20 g
Tare range	-60 kg
OIML Class	III

Physical parameters	
Display	5,7" resistive colour touchscreen
Weighing pan dimensions	400×500 mm
Communication interface	
Communication interface	2×RS232, 2×USB-A, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Electrical parameters	
Power supply	100 ÷ 240 V AC 50 / 60 Hz
Environmental conditions	
Operating temperature	-10 ÷ +40 °C
Relative humidity	10% ÷ 85% RH no condensation

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories

Receipt Printer
 Displays
 Barcode scanners
 Label Printers
 Cigarette lighter receptacle power supply cables
 USB Hubs
 IN/OUT Cables

Keypad, external switches
 Stands, wall mounting kits and mounting brackets
 F1 Mass Standard - knob weights without adjustment chamber, set
 AP2-1 Current Loop Unit
 RS 232, RS 485 cables
 RS 232 – USB Converter
 RS 232 cables (scale - EPSON printer)

Software

E2R System
 Audit Trail Reader
 RADWAG Connect
 RADWAG Remote Desktop
 RADWAG Development Studio
 Scales Editor 2.0

RAD-KEY
 LabVIEW Driver
 Label Editor R02
 R-LAB
 R.Barcode