2.1 2020



Stereomicroscope, with fixed arm, 20x-40x, touch panel, with rechargeable battery

Observation Method -	Brightfield	Yes
Transmitted Light		
Observation Method - Incident Light	Brightfield	Yes
Head	Time	Binocular
neau	Type Construction material	
	Inclination	Aluminum & Plastic molds / Aluminum gears 45°
	360° rotating	Yes
	Interpupillary distance (mm)	53-75
	Dioptric adjustment	On both tubes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	30.5
	[- ,	1
Eyepieces	Field number (mm)	20
	Magnification	10x
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	20
	Rubber cup	Yes
Objective	Ontical contour	One are according
Objective	Optical system	Greenough
	Anti-fungus treatment	Yes
	Objective Type	Achromatic
	Working distance (mm)	76
	Standard magnifications	20x, 40x (rotating turret)
Focusing System	Туре	Coarse
rocusing system	Coarse total travel (mm)	37
	` '	Yes
	Adjustable tension	res
Stand	Type	Fixed arm
Stand	Type	
	Handle	Yes
Stage	Frosted diffusion plate for transmitted ill.	Yes, diameter 60 mm
Staye	Black/white contrast plate for incident ill.	Yes, diameter 60 mm
	Specimen clips	Yes Yes
	Specimen clips	162

Transmitted	Туре	LED
Illumination	Light source power (W)	1
	Brightness control	Touch Panel
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1.5
Incident Illumination	Туре	LED
	Light source power (W)	1
	Brightness control	Touch Panel
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1.5
Power Supply for Illumination	Туре	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 500 mA
	LED indicator	Yes
	Rechargeable batteries	Yes
	Battery type	Ni-MH (3x, AA size)
	Working time of batteries (hours)	up to 8
	Charging time of batteries (hours)	8
Accessories Included	Dust cover	Yes
	Tension adjustment tool	Yes
	User Manual	Digital version (downloadable)
	-	
Additional Information	Maximum sample height (mm):	32
Product Dimensions	Total height (mm)	288
	Base height (mm)	45
	Base width (mm)	183
	Base depth (mm)	205
Product Weight	(kg)	1.9