



Binocular stereomicroscope, 20x, with overhanging stand

| | | |
|--|-----------------------------------|---|
| Observation Method - Incident Light | Brightfield | Yes |
| Head | Type | Binocular |
| | Construction material | Aluminum & Plastic molds / Aluminum gears |
| | Inclination | 45° |
| | Interpupillary distance (mm) | 53-78 |
| | Dioptric adjustment | On left tube |
| | Fixing screw for eyepieces | Yes |
| | Tube inner diameter (mm) | 30.5 |
| Eyepieces | Field number (mm) | 20 |
| | Magnification | 10x |
| | Micrometric scale | As optional |
| | Diameter of micrometer glass (mm) | 20 |
| | Rubber cup | Yes |
| Objective | Optical system | Greenough |
| | Anti-fungus treatment | Yes |
| | Objective Type | Achromatic |
| | Working distance (mm) | 119 |
| | Standard magnifications | 20x |
| Focusing System | Type | Coarse |
| | Coarse total travel (mm) | 41 |
| | Adjustable tension | Yes |
| Stand | Type | Simple overhanging |
| Incident Illumination | Type | LED |
| | Light source power (W) | 1 |
| | Lifetime (hours) | > 65,000 |
| | Temperature (K) | 6,300 |
| | Max. required power (W) | 1.5 |
| Power Supply for Illumination | Type | External |
| | Microscope connector | Jack, 2.1 mm |
| | Power plug type | Multi-plug (EU, UK, US) |
| | Input voltage | 110/240 Vac, 50/60 Hz |
| | Output voltage | 6 Vdc 2.5 A |
| Accessories Included | Dust cover | Yes |
| | Tension adjustment tool | Yes |
| | User Manual | Digital version (downloadable) |
| Additional Information | Maximum sample height (mm): | 120 (from bench) |
| Product Dimensions | Total height (mm) | 280 |
| | Base height (mm) | 65 |
| | Base width (mm) | 118 |
| | Base depth (mm) | 420 |
| | Horizontal arm (mm) | 295 |
| Product Weight | (kg) | 5 |