

Lovibond® Colour Measurement Tintometer® Group



AF329 Platinum-Cobalt/Hazen/APHA Units

Visual Color Grading of Platinum-Cobalt/Hazen/APHA Color (Range 0 - 250 mg)



- Ideal for Light Yellow Liquids such as Water, Oils and Chemicals
- Fast, Economical & Portable Visual Matching
- Two-Field Vision for Accurate Results
- Ability to Guarantee Constant Lighting Conditions

Part Number: 433290

Greater Measurement Sensitivity and Accuracy

The Lovibond® AF329 is a special kit for visual color grading using Platinum-Cobalt/Hazen/APHA Color over the range 0 - 250 mg Pt/l. It is typically used for light yellow liquids such as water, oils and chemicals. The color is determined by visually matching a column of sample in a Nessler cylinder with precalibrated colored glass standards, which are stablecolored and not affected by UV light or extreme environmental conditions. Because the sample colors are relatively unsaturated, the kit employs a long path length Nessleriser comparator to give accurate readings.

Fast, Economical & Portable Visual Matching

The Comparator 2000+ is a flexible, modular system for Visual Color Grading. Using a suitable comparator instrument and glass disc, you can quickly visually match the sample directly against the calibrated, color stable glass standards.

Two-Field Vision for Accurate Results

Lovibond® comparator instruments include an integrated prism which causes the sample and comparison fields to overlap, allowing enhanced color discrimination and matching. The prism is ultrasonically sealed to prevent contamination of the optics. Each individually graded glass standard represents a discrete step on the measurement range (as opposed to a continuous graduation), aiding color discrimination and allowing great accuracy of results.

Ability to Guarantee Constant Lighting Conditions

An optional item for the Comparator 2000+ is the Daylight 2000 Lighting Unit. This is a standardized light source which guarantees you a constant lighting condition for accurate color grading. This is particularly useful when the sample is very pale in color. By using a

Lovibond® lighting unit, you can be confident of uniform lighting conditions for color matching, 24 hours a day and irrespective of ambient lighting.

Extended Shelf Life

The unique feature of Lovibond® test discs is that they incorporate colored glass standards that are color stable and not affected by UV light or extreme environmental conditions.

Please note, we cannot guarantee compatibility of discontinued Lovibond® Comparator 1000 disks with the Lovibond® 2000+ Comparator.

Industry

Chemical Industry | Food and Beverage Industry | Oil and Gas |
Pharmaceutical Industry

Application

Chemicals | Edible Oils and Fats | Petroleum Oils and Waxes |
Pharmaceuticals and Cosmetics

AF329 Platinum-Cobalt/Hazen/APHA Units

The Lovibond® AF329 is a special kit for visual color grading using Platinum-Cobalt/Hazen/APHA Color over the range 0 - 250 mg Pt/l. It is typically used for light yellow liquids such as water, oils and chemicals. Because the sample colors are relatively unsaturated, the kit employs a long path length Nessleriser comparator to give greater measurement sensitivity and accuracy. The Comparator 2000+ is an easy-to-use, entry level color measurement system that compares the color of the sample directly against the color of glass in a disc. All you need to do is rotate the disc to get the closest result to the scale.

Delivery Scope

- 1 x Nessleriser Daylight 2000+
- 1 x Stand for Nessleriser Unit
- 1 x NSB Hazen scale disc
- 1 x CAA Hazen scale disc
- 1 x CAB Hazen scale disc
- 1 x 2150 Nessleriser body
- 1 x 2250 Nessleriser body
- 1 x Pair of Nessler cylinder AF306P
- 1 x Pair of Nessler cylinders 250mm DB420

Technical Data

Applicable Standard ASTM D1209
ISO 6271

Color Type Transparent

Portability Portable

Tintometer GmbH
Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited
Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China
Room 1001, China Life Tower
16 Chaoyangmenwai Avenue,
Beijing, 100020
Tel.: +86 10 85251111 App. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia
Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil
Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@tintometer.com.br
www.lovibond.com.br
Brazil

Tintometer Inc.
6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.com
USA

Tintometer India Pvt. Ltd.
Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain
Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain

Technical changes without notice
Printed in Germany

Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies