Lovibond[®] Colour Measurement Tintometer[®] Group



Petroleum Oils Comparator (AF650)

ASTM Oils Scale, 3-Field Visual Measurement



Accurate Determination of the ASTM Oils Scale

The AF 650 incorporates 16 glass standards which make up the scale in a pair of discs

Fast Determination of Color Value

You can directly compare the sample with the color values for quick results.

Easy to Achieve Optimum Color Accuracy

The advantage of a 3-section field of view is that the sample and two consecutive glasses on the color scale are viewed simultaneously, making it easier and quicker for you to achieve the ideal color match.

Facilitates Tolerance Level Setting

For rapid color grading within predetermined color limits, the glass standards can be set to the two limiting colors so that it is easy to check that the sample is within tolerance.

Guaranteed Constant Lighting Conditions

In the instruments, the tungsten halogen light source is color corrected to CIE standard illuminant C*, which guarantees constant lighting conditions for color grading.

Compliance to Standards

Each Comparator 3000 is supplied with the correct cells for the appropriate path length determined by the standard.

* In the EBC version, the C filter is replaced by the B filter as required by the standards.

- Compact, Visual Measurement System for Single Scale Measurements
- Self-Contained, Includes Everything Needed to Measure the Scale
- Easy-To-Use, Fast & Accurate
- 3-Field Viewing for Optimum Accuracy

Part Number: 345030

Industry

Oil and Gas

Application

Petroleum Oils and Waxes

Petroleum Oils Comparator (AF650)

A 3-field instrument for visually determining the color of petroleum oils & waxes samples according to the ASTM Color scale by direct comparison with colored glass filters.

Technical Data

Applicable Standard	ASTM D1500 ASTM D6045 ISO 2049
Color Type	Transparent
Portability	Benchtop

Delivery Scope

Comparator 3000
1 Pair glass discs

 0.5, 1.5, 2.5, 3.5, 4.5, 5.5, 6.5, 7.5
 1.0, 2.0, 3.0, 4.0, 5.0, 6.0, 7.0, 8.0

3 x Cylindrical glass sample jars

Tintometer GmbH

Lovibond® Water Testing Schleefstraße 8-12 44287 Dortmund Tel.: +49 (0)231/94510-0 sales@lovibond.com www.lovibond.com Germany

Tintometer Brazil

Caixa Postal: 271 CEP: 13201-970 Jundiaí – SP Tel.: +55 (11) 3230-6410 sales@tintometer.com.br www.lovibond.com.br Brazil

The Tintometer Limited Lovibond House Sun Rise Way

Amesbury, SP4 7GR Tel.: +44 (0)1980 664800 Fax: +44 (0)1980 625412 sales@lovibond.uk www.lovibond.com UK

Tintometer Inc. 6456 Parkland Drive Sarasota, FL 34243 Tel: 941.756.6410 Fax: 941.727.9654 sales@lovibond.us www.lovibond.com USA

Tintometer China

Room 1001, China Life Tower 16 Chaoyangmenwai Avenue, Beijing, 100020 Tel.: +86 10 85251111 App. 330 Fax: +86 10 85251001 chinaoffice@tintometer.com www.lovibond.com China

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3nd & 4th Floor Sanathnagar Industrial Estate, Hyderabad, 500018 Telangana Tel: +91 (0) 40 23883300 Toll Free: 1 800 599 3891/ 3892 indiaoffice@lovibond.in www.lovibondwater.in India

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard, Lebuh Nilam 2, Bandar Bukit Tinggi, Klang, 41200, Selangor D.E Tel.: +60 (0)3 3325 2285/6 Fax: +60 (0)3 3325 2287 lovibond.asia@tintometer.com www.lovibond.com Malaysia

Tintometer Spain

Postbox: 24047 08080 Barcelona Tel.: +34 661 606 770 sales@tintometer.es www.lovibond.com Spain

Technical changes without notice Printed in Germany Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies