

Lovibond® Colour Measurement Tintometer® Group



RT400 (diffuse/8) 8 mm aperture

Easy, Cost Sensitive Sphere Colour Spectrophotometer



- Sphere Technology with 8 mm Measurement Area / 13 mm Target Window
- Ability to Output Simultaneous SPIN/SPEX
- Storage for up to 4,000 Reference Samples
- Fully Portable with Optional Dual-Bay Charging

Part Number: 400400

Capable and Flexible

The 8mm measurement aperture and the ability to output simultaneous SPIN/SPEX measurements makes the RT 400 instrument possible the most flexible in its class.

You can use it in production or in the field to take quick colour measurements and compare the accuracy with proven results - not guess work from visual comparison. It is equally applicable for reflective measurements or uneven surfaces.

Inter-Instrument Agreement

The RT 400 supports embedded transforms that optimize agreement with benchtop instruments and improve inter-instrument agreement. You can be sure that all the results throughout the supply chain are accurate and compliant even when taken by a variety of spectrophotometers.

Storage

The instrument provides access to up to 4,000 reference samples which have been stored for fast access to existing data.

Ideal for Off-Site Measurements

The RT 400 is ideal for use in the field. The optional dual-bay charging facility helps you increase your instrument's up-time by letting you simultaneously charge the second battery.

Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Oil and Gas | Pharmaceutical Industry

Application

Chemicals | Coatings | Food and Beverage | Household Products | Medical and Clinical Products | Pharmaceuticals and Cosmetics | Plastics | Textiles

RT400 (diffuse/8) 8 mm aperture

Portable spectrophotometers provide the perfect opportunities for you to measure colour anywhere in your facilities. They are rugged yet accurate and easy to carry so you are ready to measure whenever required.

Technical Data

Applicable Standard	ASTM 313 ASTM D1925 ASTM E308
Colour Type	Transparent Translucent Opaque
Spectral Interval	10 nm - measured; 10nm - output
Measurement Range	0 tot 200 % reflectie
Measurement Time	Approx 2 seconds
Lamp Life	Approx 500,000 measurements
Storage Temperature	-4 to 122°F (-20° to 50°C)
Spectral Range	400 - 700 nm
Portability	Benchtop

Delivery Scope

Sturdy Box Including

- Instrument
- Calibration box
- Universal power supply
- Instruction manual

Accessories

Title	Part Number
RT300/400/500 Benchtop Stand	400620
RT300/400/500 Lqd Cell Holder	400630
RT300/400/500 Powder Cell Holder	400640
RT V-Block Sample Holder	400660
RT300/400/500 Pellet Holder	400680

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

Room 1001, China Life Tower
16 Chaoyangmenwai Avenue,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 App. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain