

# Lovibond<sup>®</sup> Colour Measurement Tintometer<sup>®</sup> Group



## RT505 (diffuse/8) 4 mm aperture

Portable Sphere Spectrophotometer for Multiple Applications



- Sphere Technology with 4 mm Measurement Area / 6.5 mm Target Window
- Ability to Output Simultaneous SPIN, SPEX and Correlated Gloss Measurements
- Access to up to 4,000 Reference Samples for Fast Access to Existing Data
- Fully Portable with Optional Dual-Bay Charging

Part Number: 400504

### Capable and Flexible

The 4 mm measurement aperture and the ability to output simultaneous SPIN, SPEX and Correlated Gloss measurements makes the RT 500 instrument extremely flexible.

You can use it in production or in the field to take quick colour measurements and compare the accuracy with proven results - not guess work from visual comparison. It is equally applicable for reflective measurements or uneven surfaces.

### Hands-Free Measurement

The remote measurement trigger enables you to operate the instrument remotely.

### Storage

The instrument provides access to up to 4,000 reference samples which have been stored for fast access to existing data.

### Ideal for Off-Site Measurements

The RT 500 is ideal for use in the field. The optional dual-bay charging facility helps you increase your instrument's up-time by letting you simultaneously charge the second battery.

### Ensures Your Brand Identity

If you are using metallics, special finishes and textures to gain market presence, your brand must be important to you. Colour measurement throughout your production process results in your end products always looking the same and building on your quality brand.

### Enhanced Quality Software Control

The RT 505 can be combined with the OnColor<sup>™</sup> software package allowing you to download measurement data, analyse in detail and store indefinitely on a PC.

## Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Oil and Gas | Pharmaceutical Industry

## Application

Chemicals | Coatings | Food and Beverage | Household Products | Medical and Clinical Products | Pharmaceuticals and Cosmetics | Plastics | Textiles

## RT505 (diffuse/8) 4 mm aperture

Portable sphere spectrophotometer with extreme flexibility for multiple applications. An ideal mid-range solution if you are looking for accurate colour measurement.

## Technical Data

<b>Applicable Standard</b>	ASTM 313 ASTM D1925 ASTM E308
<b>Colour Type</b>	Transparent Translucent Opaque
<b>Spectral Interval</b>	10 nm - measured; 10nm - output
<b>Measurement Range</b>	0 tot 200 % reflectie
<b>Measurement Time</b>	Approx 2 seconds
<b>Lamp Life</b>	Approx 500,000 measurements
<b>Storage Temperature</b>	-4 to 122°F (-20° to 50°C)
<b>Spectral Range</b>	400 - 700 nm
<b>Portability</b>	Benchtop

## Delivery Scope

- Sturdy Box Including Instrument
- Calibration box
- Universal power supply
- Instruction manual

## Accessories

Title	Part Number
RT On-Colour Premium Software	400610
RT300/400/500 Benchtop Stand	400620
RT300/400/500 Lqd Cell Holder	400630
RT300/400/500 Powder Cell Holder	400640
RT300/400/500 Pellet Holder	400680

### Tintometer GmbH

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
sales@lovibond.com  
www.lovibond.com  
Germany

### The Tintometer Limited

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
Fax: +44 (0)1980 625412  
sales@lovibond.uk  
www.lovibond.com  
UK

### Tintometer China

Room 1001, China Life Tower  
16 Chaoyangmenwai Avenue,  
Beijing, 100020  
Customer Care China Tel.: 4009021628  
Tel.: +86 10 85251111 App. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

### Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,  
Lebuh Nilam 2, Bandar Bukit Tinggi,  
Klang, 41200, Selangor D.E  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malaysia

### Tintometer Brazil

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@lovibond.us  
www.lovibond.com.br  
Brazil

### Tintometer Inc.

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.us  
USA

### Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
India

### Tintometer Spain

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Spain