



TwinCool ULT Freezer With Touch Screen

Scope of Application

The TwinCool ULT freezer can be used for the storage and protection of valuable samples which require strict and continuous storage conditions, designed to operate even in the event of a compressor failure. Suitable for viruses, pathogens, blood cells and other biological sample cold storage applications found within hospitals, disease control, research institutions and biomedical engineering. Also used to store special materials and other products within electronics and chemicals industries.

Innovative & Ergonomic Design

- Energy Saving Refrigeration
- Low Noise Design
- Pressure Equalization Port
- Cloud Data Storage Available
- Optimized Insulation
- Multiple Alarms

Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
Tel: +86-0532-88935593
Website: www.haiermedical.com



Intelligent TwinCool Refrigeration System

Two independent refrigeration systems are designed to ensure optimal reliability, longevity and efficiency. Depending on the load demands and ambient conditions, one or both refrigeration systems will operate on demand, ensuring the samples are fully protected under the worst possible conditions.

Product Advantages



Dual independent refrigeration systems for maximum sample safety

The dual refrigeration systems run independently and alternately, both reaching -80°C , such that if one system fails the other will maintain temperature to ensure sample storage safety.

High speed refrigeration system for faster pull down and temperature recovery after door opening

Utilizing auto-cascade hydrocarbon (HC) refrigeration technology to deliver fast temperature pull down. From an ambient of 25°C it takes just 180 minutes to reach -80°C . It provides a quick temperature recovery to -75°C within 25 minutes after door opening for 1 minute, guaranteeing the safety of samples.

World-leading energy saving refrigeration technology

The HC refrigeration technology coupled with superinsulation, increases the insulation efficiency by 30%, and the cabinet is designed to reduce heat loss ensuring an energy efficient freezer. The 418L model has a power consumption of 8.45 kWh/day and is certified by The National Quality Certification Center for Energy Saving and Environmental Protection.



DW-86L578ST

TwinCool ULT Freezer With Touch Screen

Advanced Hardware System



Smart Full-size Touch Screen

10-inch touch screen with state-of-the-art user interface design, coupled with a sample management system which provides an optimal user experience.

Optional IoT Software System



Simplified Sample Management Experience

Optional barcode scanner for simple, effortless and precise identification. Input and retrieve your samples with higher precision and efficiency.



Wireless Monitoring Connectivity

Check the real-time operating status via mobile phones or portable tablet, simple and reliable.

Innovative & Ergonomic Design



Safe and secure

Equipped with key lock, padlock and optional electromagnetic lock, with optional fingerprint lock, providing multiple safeguards for sample safety.



Cloud data storage available

Store hundreds of millions of scientific research and sample information in the cloud server.



Low noise design, reducing the noise down to 53dB

Special noise-reduction design plus super silent compressor technology and energy-saving fan, considerably lowers noise level.



Optimized insulation

Double foaming for both inner and outer doors and five-layer sealing design and optimized super-thick VIP thermal insulation technology, extends temperature holdover time during power failure and increases insulation efficiency by 30%.

TwinCool ULT Freezer With Touch Screen

Specifications



Model		DW-86L578ST	DW-86L578SAT	DW-86L728ST	DW-86L728SAT			
Technical Data	Cabinet Type	Upright		Upright				
	Climate Class	N		N				
	Cooling Type	Direct cooling		Direct cooling				
	Defrost Mode	Manual		Manual				
	Refrigerant	HC		HC				
	Sound Level (dB(A))	53	52	53	50	53		
Performance	Cooling Performance (°C)	-86		-86				
	Temperature Range (°C)	-40--86		-40--86				
Control	Controller	Microprocessor		Microprocessor				
	Display	LCD Touchscreen		LCD Touchscreen				
Electrical Data	Power Supply (V/Hz)	220-240/50	120/60	208-230/60	208-230/50	120/60	208-230/60	
	Electrical Current (A)	10	18	10	10	18	10	
	Power Consumption (kWh/24h)	12	10	10	12	11	12	
Construction	Capacity (L/Cu.Ft)	578/20.4		578/20.4		728/25.7		
	Net/Gross Weight (approx)	kg	325/355		325/355		350/385	
		lbs	716.5/782.6		716.5/782.6		771.6/848.8	
	Interior Dimension (W*D*H)	mm	620*716*1310		620*716*1310		766*716*1310	
		in	24.4*28.2*51.6		24.4*28.2*51.6		30.2*28.2*51.6	
	Exterior Dimension (W*D*H)	mm	895*998*1980		895*998*1980		1046*998*1980	
		in	35.4*39.3*78.0		35.4*39.3*78.0		41.2*39.3*78.0	
Packing Dimension (W*D*H)	mm	950*1055*2150		950*1055*2150		1100*1105*2150		
	in	37.4*41.5*84.6		37.4*41.5*84.6		43.3*43.5*84.6		
Loading Quantities	Container Load (20'/40'/40'H)	12/24/24		12/24/24		10/20/20		
Alarms	High/Low Temperature	Y		Y		Y		
	Hot Condenser	Y		Y		Y		
	Power Failure	Y		Y		Y		
	High/Low Voltage	Y		Y		Y		
	Sensor Error	Y		Y		Y		
	Low Battery	Y		Y		Y		
	High Ambient Temperature	Y		Y		Y		
	Door Ajar	Y		Y		Y		
Accessories	Caster	Y		Y		Y		
	Foot	Y		Y		Y		
	Porthole	Y/2		Y/2		Y/2		
	Shelves/Inner Doors	3/4		3/4		3/4		
	USB Interface	Y		Y		Y		
	Remote Alarm (Dry contacts)	Y		Y		Y		
	5V Power Supply Port	Y		Y		Y		
	Temperature Recorder	Optional		Optional		Optional		
	RS485 Port	Y		Y		Y		
	CO ₂ Backup System	Optional		Optional		Optional		
LN ₂ Backup System	Optional		Optional		Optional			
Certifications	CE	Y	/	/	Y	/	/	
	UL	/	Y	Y	/	Y	Y	
	ENERGY STAR	Y	Y	Y	Y	Y	Y	

Product appearance and specifications are subject to change without notice